



NOTES:

1. ALL EXPOSED METALLIZED AREA SHALL BE GOLD PLATED 60 MICRO INCHES MIN. THK. OVER NICKEL PLATE UNLESS OTHERWISE SPECIFIED IN PURCHASE ORDER.
2. FLATNEDD PERTAINS TO METALLIZED PADS ONLY.
3. SEAL AREA AND DIE ATTACH AREA SHALL BE ISOLATED FROM ANY LEADS. (ZERO GROUND)
4. LEAD RESISTANCE : 0.18 OHMS. MAX.

5.

PART NO.	KC NAME	METALLIZATION	
		SEAL RING	DIE ATTACH
01	IEB-68CZ	WITH	WITH
02		WITHOUT	WITHOUT

宜特科技股份有限公司
Integrated Service Technology Inc.

TITLE		GENERAL TOLERANCE			
68LCC(PB-C87671-B-01-JMI)					
CERTIFIED FOR CONSTRUCTION	DWG.	DESIGN	CHK.	APPR.	
BY _____	BY _____				
DATE _____	DATE _____				
LCYCIC: _____	PROJ. NO. _____	DWG. NO. LCC-068-04	REV. _____		
KPEC: _____	FILE NAME: _____	SCALE: _____	SHEET _____		

單位:Inch